



WORLD-LIFT
WFE 50-80



WFE 50- 80
5,000 lb - 8,000 lb
Electric - Pneumatic Tire

FAMILY OWNED SINCE 1975



WFE 50- 80

FEATURES & BENEFITS

- Electric 48V 630AH WFE50; 80V 500AH WFE60; 80V 550 AH WFE80
- Spacious work place: Ample leg room helps to provide a relaxed working environment keeping the operator focused throughout the working day for maximum productivity.
- Right side Hydraulic operation handle and emergency power-off button.
- High visibility design mast with side thrust rollers in the carriage for smoother operation and longer life of the mast components.
- Fully Hydrostatic Power Steering for smoother operation and many fewer parts for lower maintenance costs. This utilizes the largest cylinder and thickest steel for protection of any forklift in its class!
- Large hydraulically actuated Drum & Shoe type brakes for positive braking performance and ease of maintenance. Mechanical lever type parking brake for reliability.
- Control Handles are mounted on the dash for operator convenience and also allows the operator to enter/exit the operator compartment from either side of the machine comfortably



- Tilt Steering Wheel
- Adjustable Seat
- Seat Belt
- Dual Head Lights
- Front Turn Signals
- Rear Turn Signals
- Brake Lights
- Back-up Lights
- Back-up Alarm
- Neutral Safety Switch
- Welded Overhead Guard
- Waterproof LCD Instrument
- Integral Hydraulic Tank

- Side Mounted Motor Pump
- Low non-slip pedal
- Insulated battery cover
- Hand hold for entry
- Hood cover 90 Deg. Open
- Third valve & lever
- Horn
- Hour Meter
- Charge warning light
- Temperature warning light
- Hyd pressure gauge
- Key switch
- Safety load backrest

- ITA Class II or III forks & carriage
- Easy access floor boards
- Rubber safety mat
- Meet or exceed all ANSI B56.1
- Safety standards for powered industrial trucks and underwriters laboratories requirements as to fire hazard. EPA Compliant



FEATURES & BENEFITS

MODEL		WFE 50	WFE 60	WFE 80	Notes
Capacity	Lbs	5,000	6,000	8,000	
Load Center	Inch	24	24	24	
Power		Electric-AC	Electric-AC	Electric -AC	
Tires Solid Pneumatic		7-12-12 Pr	28 X9-15-12	28X9-15-12pr	Front
Drive Motor	kw	11	15	15	
Fork Size	Inch	42	42	42	
Length	Inch	93	100.8	100.8	Add fork length
Mast Tilt Fwd/Back	Deg.	6 / 12	6 / 12	6 / 12	
Total Width	Inch	45.7	48.4	48.4	
Mast Height Lowered	Inch	83.5	83.5	83.5	Std 2 stage mast
Guard Height	Inch	88	88.6	88.6	
Min Turn Radius Outside	Inch	81.7	91	91	
Max Height	Inch	158	158	158	With LBR
Min Intersecting Aisle	Inch	88.6	95.5	95.5	
Ground Clearance	Inch	4.3	4.7	4.7	Bottom of Mast
Service Weight	Lb	9,193	11,244	11,795	Includes battery
Wheel Base	Inch	59.5	67	67	
Travel Speed	MPH	9.3	9.3	9.3	No Load
Lifting Speed Per Sec	Inch	11.8	11.8	11.0	Full Load
Brakes	Type	Hand/Foot	Hand/ Foot	Hand/Foot	
Fork Spread Min/Max	Inch	9.5/40.2	9.8/43	9.8/43	
Max Gradeability	Deg	15	15	15	

Standard Equipment

- Two Stage Mast
- Pneumatic Tires
- Curtis Controls
- Tier IV
- Drive Motor
- Headlights
- Back Up Lights
- Turn Signals
- Hydro Steer Axle
- Mirrors
- Load Backrest
- Seat Belt
- Tilt Steer Wheel
- 3rd Valve
- Operator Manual
- Standard Forks

Optional Equipment

- Various Masts
- Standard
- Full Free Lift Triplex
- Various Tire Options
- Solid
- Non Marking
- Treaded
- Side Shifter
- Fork Positioner
- 4 Way Hydraulics
- Much More!



MOVING STUFF, SINCE 1945

954-768-9875

worldwideforklifts.com

